

07-03-00

A

06/30/00
U.S. PTO
UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
13768.143Total Pages in this Submission
3**TO THE ASSISTANT COMMISSIONER FOR PATENTS**Box Patent Application
Washington, D.C. 20231

Transmitted herewith for filing under 35 U.S.C. 111(a) and 37 C.F.R. 1.53(b) is a new utility patent application for an invention entitled:

METHODS AND SYSTEMS FOR PREVENTING SOCKET FLOODING DURING DENIAL OF SERVICE ATTACKS

and invented by:

Bilal Alam and Michael Courage

U.S. PRO
JC657 607500
06/30/00If a **CONTINUATION APPLICATION**, check appropriate box and supply the requisite information: Continuation Divisional Continuation-in-part (CIP) of prior application No.: _____

Which is a:

 Continuation Divisional Continuation-in-part (CIP) of prior application No.: _____

Which is a:

 Continuation Divisional Continuation-in-part (CIP) of prior application No.: _____

X Application claims priority to US provisional application serial number 60/189,096 filed 14 March 2000

Enclosed are:

Application Elements

1. Filing fee as calculated and transmitted as described below

2. Specification having 28 pages and including the following:
 - a. Descriptive Title of the Invention
 - b. Cross References to Related Applications (*if applicable*)
 - c. Statement Regarding Federally-sponsored Research/Development (*if applicable*)
 - d. Reference to Microfiche Appendix (*if applicable*)
 - e. Background of the Invention
 - f. Brief Summary of the Invention
 - g. Brief Description of the Drawings (*if drawings filed*)
 - h. Detailed Description
 - i. Claim(s) as Classified Below
 - j. Abstract of the Disclosure

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
13768.143

Total Pages in this Submission
3

Application Elements (Continued)

3. Drawing(s) (*when necessary as prescribed by 35 USC 113*)
 - a. Formal Number of Sheets 5
 - b. Informal Number of Sheets _____
4. Oath or Declaration
 - a. Newly executed (*original or copy*) Unexecuted
 - b. Copy from a prior application (37 CFR 1.63(d)) (*for continuation/divisional application only*)
 - c. With Power of Attorney Without Power of Attorney
 - d. **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 C.F.R. 1.63(d)(2) and 1.33(b).
5. Incorporation By Reference (*usable if Box 4b is checked*)
The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.
6. Computer Program in Microfiche (*Appendix*)
7. Nucleotide and/or Amino Acid Sequence Submission (*if applicable, all must be included*)
 - a. Paper Copy
 - b. Computer Readable Copy (*identical to computer copy*)
 - c. Statement Verifying Identical Paper and Computer Readable Copy

Accompanying Application Parts

8. Assignment Papers (*cover sheet & document(s)*)
9. 37 CFR 3.73(B) Statement (*when there is an assignee*)
10. English Translation Document (*if applicable*)
11. Information Disclosure Statement/PTO-1449 Copies of IDS Citations
12. Preliminary Amendment
13. Acknowledgment postcard
14. Certificate of Mailing
 First Class Express Mail (*Specify Label No.:* EL624147293US)

UTILITY PATENT APPLICATION TRANSMITTAL
(Large Entity)

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Docket No.
13768.143

Total Pages in this Submission
3

Accompanying Application Parts (Continued)

15. Certified Copy of Priority Document(s) *(if foreign priority is claimed)*

16. Additional Enclosures *(please identify below):*

Fee Calculation and Transmittal

CLAIMS AS FILED

For	#Filed	#Allowed	#Extra	Rate	Fee
Total Claims	25	- 20 =	5	x \$18.00	\$90.00
Indep. Claims	3	- 3 =	0	x \$78.00	\$0.00
Multiple Dependent Claims (check if applicable)	<input type="checkbox"/>				\$0.00
				BASIC FEE	\$690.00
OTHER FEE (specify purpose)					\$0.00
				TOTAL FILING FEE	\$780.00

A check in the amount of **\$780.00** to cover the filing fee is enclosed.

The Commissioner is hereby authorized to charge and credit Deposit Account No. **23-3178** as described below. A duplicate copy of this sheet is enclosed.

Charge the amount of _____ as filing fee.

Credit any overpayment.

Charge any additional filing fees required under 37 C.F.R. 1.16 and 1.17.

Charge the issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance, pursuant to 37 C.F.R. 1.311(b).

Signature

Dated: **June 30, 2000**

Adrian J. Lee
Attorney for Applicant
Registration No. 42,785
WORKMAN, NYDEGGER & SEELEY
1000 Eagle Gate Tower
60 East South Temple
Salt Lake City, Utah 84111

cc:

CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10)

Applicant(s): Bilal Alam and Michael Courage

Docket No.

13768.143

Serial No.

Filing Date

Examiner

Group Art Unit

Invention:

METHODS AND SYSTEMS FOR PREVENTING SOCKET FLOODING DURING DENIAL OF SERVICE ATTACKS

I hereby certify that this Transmittal letter (in duplicate) (*and other documents)
(Identify type of correspondence)

is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under
37 CFR 1.10 in an envelope addressed to: The Assistant Commissioner for Patents, Washington, D.C. 20231 on
June 30, 2000

(Date)

Mandy Jensen

(Typed or Printed Name of Person Mailing Correspondence)

A handwritten signature of 'Mandy Jensen' over a horizontal line.

(Signature of Person Mailing Correspondence)

EL624147293US

("Express Mail" Mailing Label Number)

Note: Each paper must have its own certificate of mailing.

* Patent Application (28pgs)
5 Sheets of Formal Drawings
Check No. 116393 in the amount of \$780.00
Postcard

UNITED STATES PATENT APPLICATION

of

Bilal Alam

and

Michael Courage

for

**METHODS AND SYSTEMS FOR
PREVENTING SOCKET FLOODING
DURING DENIAL OF SERVICE ATTACKS**

1

BACKGROUND OF THE INVENTION

2

1. Cross-Reference to Related Applications

3

4

5

The present application claims the benefit of United States provisional application serial number 60/189,096, filed 14 March 2000, which provisional application is incorporated herein by reference.

6

7

2. The Field of the Invention

8

9

10

The present invention relates to computer networks. Specifically, the present invention relates to methods and system for preventing socket flooding during denial of service attacks.

11

12

3. The Prior State of the Art

13

14

15

16

17

18

Computer networks, and in particular the Internet, have transformed the way people communicate and do business. In these computer networks, computer systems may often communicate using a request/response protocol. For example, a requesting client computer system (“client”) will transmit a request for a service to a responding server computer system (“server”). The responding server then uses data from within the request in order to fulfill the request.

19

20

21

22

23

24

For example, a client may compose a request for a Web page. In such a request, there would typically be request data such as the Uniform Resource Locator (“URL”) identifying the Web page, the address of the client, and any other data that would be needed or helpful for the server to retrieve the Web page and transmit that Web page to the client. For each request, a typical server would allocate resources such as memory space,

1 processing time or pooled function calls for receiving the request data. Upon processing of
2 the request data, the server would then free up these allocated resources.

3 While the vast majority of individuals use computer networks in a responsible
4 manner, there are a few individuals who maliciously desire to harm others using computer
5 networks. One particular harmful scheme is to impair the operation of another's server.
6 This may be accomplished by, for example, repeatedly transmitting requests to the server
7 without sending any request data.

8 Unaware of the malicious nature of the attack, the server will unknowingly attempt
9 to accommodate each request by allocating memory, processing time and/or pooled
10 function calls for each request. However, in the described harmful scheme, since no
11 request data is sent, the server cannot finish processing the request until it has received data
12 from the client. Until it has finished processing the request, the allocated resources are tied
13 up and unavailable for subsequent requests. The server will eventually time out the
14 connection and reclaim the resources after a certain time, but the timeout period is
15 relatively long compared to the time it takes an attacker to flood the computer with
16 requests. Eventually, during this timeout period, the server will deplete its ability to
17 allocate resources resulting in denials of service for subsequent legitimate requests during
18 the timeout period. This effectively shuts down operation of the server during the timeout
19 period resulting in a loss of service for legitimate requests.

20 Therefore, what are desired are methods and systems for reducing the incidence of
21 service denials due to an attack in which requests are repeatedly made to the server without
22 transmitting any request data.

23
24

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

SUMMARY OF THE INVENTION

The present invention relates to methods and systems for preventing or at least reducing the impact of denial of service attacks. Denial of service attacks occur when a client repeatedly sends connection requests to a server without sending corresponding request data. Without adequate protection, the server will allocate resources for each connection request. However, since no request data is sent, the server cannot finish processing the request and sits idle waiting for data from the client. The resources are hence not freed up for subsequent requests. Eventually, the resources are expended to a point where the server cannot respond to any other requests, legitimate or not. Thus, the server is effectively shut down by the denial of service attack.

In accordance with the present invention, an effective method of reducing the impact of denial of service attacks is presented. In one embodiment, the method is implemented in large part using Winsock modules. For each connection request received by the server from one or more clients, the server attempts to establish a connection to accommodate the corresponding request. In the Winsock implementation, the Winsock extension Winsock()AcceptEx() is used to try to establish a connection.

Next, the connection request is mapped to a corresponding listen socket. For each connection request that the server cannot currently handle, the connection request is placed in the backlog queue corresponding to the listen socket to which the connection request mapped. The backlog queues are monitored, for example, by calling a Winsock()select() module and passing in those listen sockets that correspond to the monitored backlog queues. The backlog queues are determined to be used, for example, if the Winsock()select() module returns.

1 If one or more of the backlog queues have entries, then the method determines
2 which connection sockets have connections but no corresponding request data. This
3 identification may be accomplished using, for example, the Winsock()getsockopt()
4 module. These connection sockets are suspected to be serving a malicious connection
5 request since there is a connection but no request data received which is indicative of a
6 denial of service attack. Thus, these connection sockets are disconnected.

7 The present invention allows for the early detection of denial of service attacks by
8 immediately taking action once the backlog queue has entries, rather than waiting until the
9 server becomes dysfunctional. If a denial of service attack were to occur, highly suspect
10 connection sockets corresponding to the denial of service attack would be disconnected
11 thereby freeing up resources for legitimate requests. Even if the denial of service attack
12 were to continue, the method would continue to disconnect the maliciously established
13 connections thereby allowing more legitimate connection requests to be satisfied even
14 during the denial of service attack. This improves the security of the server against denial
15 of service attacks and diminishes the malicious motive for generating denial of service
16 attacks in the first place.

17 There is some risk associated with closing a connection socket simply when it has a
18 connection but no received data. For example, the connection socket may not have been
19 created as a result of a malicious connection request. Instead, it may be that the connection
20 request was legitimate in that the associated connection socket just happened to be in a
21 stage where the connection was just made but the soon to arrive request data simply has
22 not arrived yet. In this case, a legitimate connection request would be denied.

23 However, this case would typically be relatively rare. For example, the legitimate
24 connection request would not be denied unless the backlog queue had entries in it which

1 should in itself be relatively rare. Secondly, even though the backlog queue is full, the
2 period of time between the time a connection is made and the time the data is received is
3 relatively brief for a legitimate connection request. Thus, the chance that the legitimate
4 connection request would be executing in that brief period is also relatively small.

5 Notwithstanding this small risk, the method may be further optimized to reduce the
6 chances for denying legitimate connection requests even further by allowing the systems
7 administrator to specifying a grace period between the time the backlog queue is
8 determined to be used and the time the identified connection sockets are disconnected. If,
9 during this grace period, the server is able to handle the connection requests in the backlog
10 queue, no connection sockets will be disconnected.

11 Additional features and advantages of the invention will be set forth in the
12 description which follows, and in part will be obvious from the description, or may be
13 learned by the practice of the invention. The features and advantages of the invention may
14 be realized and obtained by means of the instruments and combinations particularly
15 pointed out in the appended claims. These and other features of the present invention will
16 become more fully apparent from the following description and appended claims, or may
17 be learned by the practice of the invention as set forth hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

In order that the manner in which the above-recited and other advantages and features of the invention are obtained, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments thereof which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

Figure 1 illustrates an exemplary system that provides a suitable operating environment for the present invention:

Figure 2 is schematically illustrates a client and server communicating using a standard request/response protocol;

Figure 3 illustrates a server-implemented process for responding to requests;

Figure 4 illustrates a series of listen sockets implements using a Winsock module as existing on a server; and

Figure 5 illustrates a server-implemented method of protecting against or at least reducing the impact of denial of service attacks.

1

DETAILED DESCRIPTION OF THE INVENTION

2

The present invention extends to both methods and systems for preventing denial of services due to socket flooding caused by a denial of service attack. The embodiments of the present invention may comprise a special purpose or general purpose computer including various computer hardware, as discussed in greater detail below.

6

Embodiments within the scope of the present invention also include computer-readable media for carrying or having computer-executable instructions or data structures stored thereon. Such computer-readable media can be any available media which can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, such computer-readable media can comprise RAM, ROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code means in the form of computer-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a computer, the computer properly views the connection as a computer-readable medium. Thus, any such a connection is properly termed a computer-readable medium. Combinations of the above should also be included within the scope of computer-readable media. Computer-executable instructions comprise, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing device to perform a certain function or group of functions.

23

Figure 1 and the following discussion are intended to provide a brief, general description of a suitable computing environment in which the invention may be

1 implemented. Although not required, the invention will be described in the general context
2 of computer-executable instructions, such as program modules, being executed by
3 computers in network environments. Generally, program modules include routines,
4 programs, objects, components, data structures, etc. that perform particular tasks or
5 implement particular abstract data types. Computer-executable instructions, associated
6 data structures, and program modules represent examples of the program code means for
7 executing steps of the methods disclosed herein. The particular sequence of such
8 executable instructions or associated data structures represent examples of corresponding
9 acts for implementing the functions described in such steps.

10 Those skilled in the art will appreciate that the invention may be practiced in
11 network computing environments with many types of computer system configurations,
12 including personal computers, hand-held devices, multi-processor systems,
13 microprocessor-based or programmable consumer electronics, network PCs,
14 minicomputers, mainframe computers, and the like. The invention may also be practiced
15 in distributed computing environments where tasks are performed by local and remote
16 processing devices that are linked (either by hardwired links, wireless links, or by a
17 combination of hardwired or wireless links) through a communications network. In a
18 distributed computing environment, program modules may be located in both local and
19 remote memory storage devices.

20 With reference to Figure 1, an exemplary system for implementing the invention
21 includes a general purpose computing device in the form of a conventional computer 120,
22 including a processing unit 121, a system memory 122, and a system bus 123 that couples
23 various system components including the system memory 122 to the processing unit 121.
24 The system bus 123 may be any of several types of bus structures including a memory bus

1 or memory controller, a peripheral bus, and a local bus using any of a variety of bus
2 architectures. The system memory includes read only memory (ROM) 124 and random
3 access memory (RAM) 125. A basic input/output system (BIOS) 126, containing the basic
4 routines that help transfer information between elements within the computer 120, such as
5 during start-up, may be stored in ROM 124.

6 The computer 120 may also include a magnetic hard disk drive 127 for reading
7 from and writing to a magnetic hard disk 139, a magnetic disk drive 128 for reading from
8 or writing to a removable magnetic disk 129, and an optical disk drive 130 for reading
9 from or writing to removable optical disk 131 such as a CD-ROM or other optical media.
10 The magnetic hard disk drive 127, magnetic disk drive 128, and optical disk drive 130 are
11 connected to the system bus 123 by a hard disk drive interface 132, a magnetic disk drive-
12 interface 133, and an optical drive interface 134, respectively. The drives and their
13 associated computer-readable media provide nonvolatile storage of computer-executable
14 instructions, data structures, program modules and other data for the computer 120.
15 Although the exemplary environment described herein employs a magnetic hard disk 139,
16 a removable magnetic disk 129 and a removable optical disk 131, other types of computer
17 readable media for storing data can be used, including magnetic cassettes, flash memory
18 cards, digital video disks, Bernoulli cartridges, RAMs, ROMs, and the like.

19 Program code means comprising one or more program modules may be stored on
20 the hard disk 139, magnetic disk 129, optical disk 131, ROM 124 or RAM 125, including
21 an operating system 135, one or more application programs 136, other program modules
22 137, and program data 138. A user may enter commands and information into the
23 computer 120 through keyboard 140, pointing device 142, or other input devices (not
24 shown), such as a microphone, joy stick, game pad, satellite dish, scanner, or the like.

1 These and other input devices are often connected to the processing unit 121 through a
2 serial port interface 146 coupled to system bus 123. Alternatively, the input devices may
3 be connected by other interfaces, such as a parallel port, a game port or a universal serial
4 bus (USB). A monitor 147 or another display device is also connected to system bus 123
5 via an interface, such as video adapter 148. In addition to the monitor, personal computers
6 typically include other peripheral output devices (not shown), such as speakers and
7 printers.

8 The computer 120 may operate in a networked environment using logical
9 connections to one or more remote computers, such as remote computers 149a and 149b.
10 Remote computers 149a and 149b may each be another personal computer, a server, a
11 router, a network PC, a peer device or other common network node, and typically include
12 many or all of the elements described above relative to the computer 120, although only
13 memory storage devices 150a and 150b and their associated application programs 136a and
14 136b have been illustrated in Figure 1. The logical connections depicted in Figure 1
15 include a local area network (LAN) 151 and a wide area network (WAN) 152 that are
16 presented here by way of example and not limitation. Such networking environments are
17 commonplace in office-wide or enterprise-wide computer networks, intranets and the
18 Internet.

19 When used in a LAN networking environment, the computer 120 is connected to
20 the local network 151 through a network interface or adapter 153. When used in a WAN
21 networking environment, the computer 120 may include a modem 154, a wireless link, or
22 other means for establishing communications over the wide area network 152, such as the
23 Internet. The modem 154, which may be internal or external, is connected to the system
24 bus 123 via the serial port interface 146. In a networked environment, program modules

1 depicted relative to the computer 120, or portions thereof, may be stored in the remote
2 memory storage device. It will be appreciated that the network connections shown are
3 exemplary and other means of establishing communications over wide area network 152
4 may be used.

5 Figure 2 illustrates a requesting client computer system 210 (hereinafter, "a client")
6 and a responding server computer system 220 (hereinafter, "a server") which communicate
7 over a network 230. In a typical request/response communication protocol such as
8 HyperText Transport Protocol ("HTTP"), the client 210 transmits a connection request 240
9 to the server 220 over the network 230. The server 240 then provides a connection in
10 response to the connection request and transmits a connection confirmation message 250
11 back to the client 210. The client 210 then transmits request data 260 to the server 220.
12 The request data 260 includes information helpful in identifying what the request is as well
13 as information helpful in fulfilling the request. If appropriate for the request, the server
14 220 then transmits a response 270 back to the client 210 over the network 230.

15 The server computer system 220 is a "server" computer system in that it provides a
16 service in the form of a connection and a response to the client computer system 210. The
17 server may also obtain the services of other computer systems over the network. In this
18 context, the server 220 may also be a client computer system. The client computer system
19 210 is a "client" computer system in that it is served by the server providing the connection
20 and generating the response. The client computer system 210 may provide services to yet
21 other computer systems. In this context, the client computer system may also be a server
22 computer system. The client 210 and the server 220 may each be structure similar to the
23 computer 120 or may contain a subset or superset of the elements described above for the
24 computer 120.

1 Figure 3 illustrates a flowchart of a method 300 performed by the server 220 when
2 responding to requests from the client 210. The method is initiated by the server 220
3 monitoring the network 230 for connection requests destined for the server 220 (step 310).
4 The method continues as the server 220 detects such connection requests (step 320). The
5 remainder of the method 300 is performed for each detected connection request.

6 For each connection request, a connection is established using a means or step for
7 establishing a connection request. Specifically, for each connection request, the
8 connection request is mapped to a specific listen socket (step 330). If the server is
9 implementing the WINDOWS ® operating system, the server may call a Winsock module
10 to map the request to the listen socket. Figure 4 schematically illustrates a Winsock
11 module 410 and associated listen sockets 420 and will be used in describing the remaining
12 steps of Figure 3. As apparent to those of ordinary skill in the art, a listen socket allows
13 the server to listen for the expected request data. The Winsock module may create one or
14 more listen sockets 420A through 420H. Step 330 maps the request to one of these listen
15 sockets 420.

16 If the server is able to accommodate the connection request ("Yes" in decision
17 block 340), the server allocates resources (step 360) such as memory space, processing
18 time or pooled function calls for receiving and processing the expected request data. The
19 server computer system then receives the request data (step 370) and processes the request
20 data (step 380). Once the server has completed processing the request, the server frees up
21 the previously allocated resources and disconnects (step 390).

22 On the other hand, if the server 220 is unable to handle the connection request
23 ("No" in decision block 340), then the connection request is placed in a backlog queue for
24 future handling (step 350). As shown in Figure 4, each listen socket 420A through 420H

1 has a corresponding backlog queue 430A through 430H. If the server cannot handle the
2 connection request, the connection request is passed into the queue corresponding to the
3 listen socket that the connection request mapped to in step 330. Although each listen
4 socket has a request queue in Figure 4, in an alternative embodiment, a more general
5 backlog queue may be shared between one or more or all of the listen sockets. In this
6 alternative, the server computer system may map the request to the listen socket after the
7 connection request is drawn from the backlog queue during future processing.

8 The method 300 will now be explained in the context of a WINDOWS ® operating
9 system using a Winsock module to establish connections. For each detected connection
10 request, the Winsock module maps the connection request to a listen socket (step 330). To
11 establish a connection to the listen socket, a module may be called that accepts connections
12 and waits for request data before completing. For example, an extension of the Winsock
13 module called Winsock()AcceptEx() is called and the corresponding listen socket is passed
14 in along with the new connection socket that represents the connection to the listen socket.
15 The Winsock()AcceptEx() is completed when request data is beginning to be received
16 from the network in step 370.

17 Winsock may allocate a pool having a fixed number of Winsock()Accept() calls
18 available for creating new connections. If the entire pool of Winsock()Accept() calls are
19 already processing new connections, then the server is not currently able to satisfy
20 subsequent connection requests ("No" in decision block 340). In this case, the connection
21 request is placed in the backlog queue corresponding to listen socket (step 350).

22 In normal operation, it should preferably be very rare that the server 220 cannot
23 currently handle a connection request. However, a denial of service attack may often result
24 in the server being unable to currently handle connection requests. In this description and

1 in the claims, a “denial of server attack” is defined as the repetitious transmission of
2 connection requests without a subsequent transmission of request data needed to process
3 the requests. In such a denial of service attack, the method 300 of Figure 3 will proceed
4 through step 360 in which resources are allocated. However, the server does not receive
5 subsequent request data as in step 370. Therefore, the allocated resources are never freed
6 up in step 390. Since connection requests are repeatedly made, the amount of allocated
7 resources rises until the server can no longer allocate resources and thus must deny
8 legitimate requests for service.

9 In the context of the Winsock module, the repeated connection requests will result
10 in repeated calls of the Winsock()AcceptEx() module. However, none of the
11 Winsock()AcceptEx() modules will complete since no request data is sent during a denial
12 of service attack. Thus, the pool of Winsock()AcceptEx() modules will gradually deplete.
13 Eventually, the server 220 will not be able to handle new connection requests, legitimate or
14 not, and the connection requests will be placed in the backlog queue. Eventually, the
15 backlog queue will also be filled up and thus new connection requests will not be saved
16 and thus will never be handled.

17 Figure 5 illustrates a flowchart of a method 500 that prevents or at least reduces the
18 impact of these denial of service attacks. As mentioned above, when the server 220 cannot
19 currently handle a connection request, the connection request is placed in a backlog queue.
20 The method 500 monitors this backlog queue (step 510). Accordingly, embodiments
21 within the scope of the present invention include a means and/or step for monitoring the
22 backlog queue. Any method of monitoring the backlog queue will suffice so long as the
23 method is capable of determining whether or not there are entries in the backlog queue. In
24 the example shown in Figure 4, each listen socket has a corresponding backlog queue. The

1 method 500 may monitor these backlog queues by, for example, calling modules that scan
2 the backlog queues to determine usage. On such module is a Winsock extension called
3 Winsock()select(). A list of listen sockets is passed into the Winsock()select() function.
4 The Winsock()select() module monitors the backlog queue of each of the listens sockets in
5 the list of listen sockets passed into the Winsock()select() module.

6 Next, the method 500 determines if the backlog queue is being used (step 520).
7 Any method for determining that the backlog queue is being used will suffice. In the
8 above example where the Winsock()select() extension of Winsock is used to monitor the
9 backlog queue, the determination is made by the very fact that the
10 Winsock()select()extension module returns. The Winsock()select() extension module
11 returns when one or more of the listen sockets have entries in their corresponding backlog
12 queues.

13 Next, the method 500 resets one or more connection sockets upon notification that
14 the backlog queue is being used (step 530). Accordingly, embodiments within the scope of
15 the present invention include a means and/or step for resetting one or more connection
16 sockets upon notification that the backlog queue is being used.

17 As part of the step for resetting one or more listen sockets, the method 500 includes
18 a step of determining which connection sockets have established connections, but have not
19 received any data (step 540). In the context of using Winsock, the server computer system
20 220 enumerates all the connection sockets that have been created using a currently called
21 Winsock()AcceptEx() function. For each of these currently called Winsock()AcceptEx()
22 connection sockets, the extension Winsock()getsockopt() is used to determine whether or
23 not a connection has been established. If a connection has been established, then the
24 connection socket is suspected of being caused by a malicious connection request since a

1 connection has been made, yet no request data has been sent (otherwise, the
2 Winsock()AcceptEx() module would not be currently called but would have been
3 completed). Thus, this connection socket may be disconnected (step 550) since it is
4 assumed that a connection socket having a connection but no request data is most likely the
5 result of a denial of service attack.

6 There is some risk associated with closing a connection socket simply because it
7 has a connection but no received request data. For example, the connection socket may not
8 have been created as a result of a malicious connection request. Instead, it may be the
9 connection request was legitimate in that the associated connection socket just happened to
10 be in a stage where the connection was just made but the soon to arrive request data simply
11 has not arrived yet. In this case, a legitimate connection request would be denied.

12 However, this case would typically be relatively rare. For example, the legitimate
13 connection request would not be denied unless the backlog queue had entries in it which
14 should in itself be relatively rare. Secondly, even though the backlog queue is full, the
15 period of time between the time a connection is made and the time the data is received is
16 relatively brief for a legitimate connection request. Thus, the chance that the legitimate
17 connection request would be executing in that brief period is also relatively small. On the
18 other hand, using this method would substantially reduce the impact of denial of service
19 attacks. Thus, the advantages of the method in reducing the impact of denial of service
20 attacks would typically outweigh the relatively small risk of denying legitimate connection
21 requests.

22 Notwithstanding this small risk, the method may be further optimized to reduce the
23 chances for denying legitimate connection requests even further. For example, the server
24 computer system 220 may be configured to allow for a specified grace period after entries

1 are detected in the backlog queue before connections are disconnected. If, during this
2 grace period, the server handles the connection requests in the backlog queue, no
3 connection sockets are disconnected.

4 The present invention may be embodied in other specific forms without departing
5 from its spirit or essential characteristics. The described embodiments are to be considered
6 in all respects only as illustrative and not restrictive. The scope of the invention is,
7 therefore, indicated by the appended claims rather than by the foregoing description. All
8 changes which come within the meaning and range of equivalency of the claims are to be
9 embraced within their scope.

10 What is claimed and desired to be secured by United States Letters Patent is:

1 1. In a networked environment, wherein one or more client computer systems
2 make requests for information from a server computer system, the server computer system
3 providing information in response to the requests from the one or more client computer
4 systems, the server computer system having one or more listen sockets and having a
5 backlog queue for queuing connection requests that the server computer system cannot
6 currently handle, a method of reducing denials of service even though the server computer
7 system is experiencing a denial of service attack, the method comprising:

8 attempting a connection for each connection request received by the server
9 computer system from said one or more client computer systems;
10 for each connection request that the server computer system cannot
11 currently handle, placing the connection request in a backlog queue;
12 monitoring the backlog queue;
13 determining that the backlog queue is being used;
14 resetting one or more connection sockets upon notification that the backlog
15 queue is being used.

16
17 2. The method in accordance with Claim 1, further comprising mapping each
18 connection request to a corresponding listen socket.

19
20 3. The method in accordance with Claim 2, wherein each listen socket has a
21 corresponding backlog queue.

1 4. The method in accordance with Claim 3, wherein placing the connection
2 request in a backlog queue comprises placing the request in the backlog queue
3 corresponding to the listen socket that the connection request mapped to.

4

5 5. The method in accordance with Claim 1, wherein attempting a connection
6 for each connection request received by the server computer system from said one or more
7 client computer systems is performed using a Winsock module.

8

9 6. The method in accordance with Claim 1, wherein attempting a connection
10 comprises calling a module that accepts connections and waits for request data before
11 completing.

12

13 7. The method in accordance with Claim 6, wherein the module that accepts
14 connects and waits for request data before completing comprises a Winsock()AcceptEx()
15 module.

16

17 8. The method in accordance with Claim 1, wherein monitoring the backlog
18 queue comprises calling a module that scans at least the backlog queue for activity.

19

20 9. The method in accordance with Claim 8, wherein determining that the
21 backlog queue is being used comprises detecting that the module that scans at least the
22 backlog queue has returned.

10. The method in accordance with Claim 8, wherein the module that scans at least the backlog queue for activity comprises a Winsock()select() module.

11. The method in accordance with Claim 10, wherein determining that the backlog queue is being used comprises detecting that the Winsock()select() module has returned.

12. The method in accordance with Claim 1, wherein resetting one or more connection sockets upon notification that the backlog queue is being used comprises the following:

identifying any connection sockets that have connections but no received request data; and

disconnecting the identified connection sockets.

13. The method in accordance with Claim 12, wherein identifying any connection sockets that have connections but no received request data comprises the following:

calling a module that identifies the state of the connection socket.

14. The method in accordance with Claim 13, wherein the module that identifies the state of the connection socket comprises a Winsock()getsockopt() module.

15. The method in accordance with Claim 1, further comprising:

specifying a grace period between the time the backlog queue is determined to be used and the time one or more connection sockets are reset to allow the server computer system to empty the backlog queue, wherein the resetting of the one or more connection sockets is performed only if the backlog queue still has entries after the grace period.

16. The method in accordance with Claim 1, wherein attempting a connection for each connection request received by the server computer system from said one or more client computer systems comprises establishing a connection.

1 17. A computer program product for use in a networked environment, wherein
2 one or more client computer systems make requests for information from a server
3 computer system, the server computer system providing information in response to the
4 requests from the one or more client computer systems, the server computer system having
5 one or more listen sockets and having a backlog queue for queuing connection requests
6 that the server computer system cannot currently handle, a computer program product for
7 implementing a method of reducing denials of service even though the server computer
8 system is experiencing a denial of service attack, wherein the computer program product
9 comprises computer-executable instructions which, when executed by a processor,
10 implements the following:

11 attempting a connection for each connection request received by the server
12 computer system from said one or more client computer systems;

13 for each connection request that the server computer system cannot
14 currently handle, placing the connection request in a backlog queue;

15 monitoring the backlog queue;

16 determining that the backlog queue is being used;

17 resetting one or more connection sockets upon notification that the backlog
18 queue is being used.

19
20 18. The computer program product in accordance with Claim 17, further
21 comprising computer-executable instructions for mapping each connection request to a
22 corresponding listen socket, wherein each listen socket has a corresponding backlog queue.

1 19. The computer program product in accordance with Claim 17, wherein the
2 computer-executable instructions for placing the connection request in a backlog queue
3 comprise computer-executable instructions for placing the request in the backlog queue
4 corresponding to the listen socket that the connection request mapped to.

5

6 20. The computer program product in accordance with Claim 17, wherein the
7 computer-executable instructions for attempting a connection for each connection request
8 received by the server computer system from said one or more client computer systems
9 comprises at least portions of a Winsock module.

10

11 21. The computer program product in accordance with Claim 17, wherein the
12 computer-executable instructions for resetting one or more connection sockets upon
13 notification that the backlog queue is being used comprise computer-executable
14 instructions for performing the following:

15 identifying any connection sockets that have connections but no received
16 request data;

17 disconnecting the identified connection sockets.

18

19 22. The computer program product in accordance with Claim 17, further
20 comprising computer-executable instructions for performing the following:

21 specifying a grace period between the time the backlog queue is determined
22 to be used and the time one or more connection sockets are reset to allow the server
23 computer system to empty the backlog queue, wherein the resetting of the one or

more connection sockets is performed only if the backlog queue still has entries after the grace period.

23. The computer program product in accordance with Claim 17, wherein the computer-executable instructions for attempting a connection for each connection request received by the server from said one or more clients comprise computer-executable instructions for establishing a connection.

1 24. In a networked environment, wherein one or more client computer systems
2 make requests for information from a server computer system, the server computer system
3 providing information in response to the requests from the one or more client computer
4 systems, the server computer system having one or more listen sockets, each listen socket
5 having a backlog queue for queuing connection requests that the server computer system
6 cannot currently handle, a method of reducing denials of service even though the server
7 computer system is experiencing a denial of service attack, the method comprising:

8 attempting a connection for each connection request received by the server
9 computer system from said one or more client computer systems using a
10 Winsock()AcceptEx() module;

11 mapping each connection request to a corresponding listen socket;

12 for each connection request that the server computer system cannot
13 currently handle, placing the connection request in the backlog queue
14 corresponding to the listen socket that the connection request mapped to;

15 monitoring the backlog queue using a Winsock()select() module;

16 determining that the backlog queue is being used by detecting that the
17 Winsock()select() module has returned;

18 identifying any connection sockets that have connections but no received
19 request data using a Winsock()getsockopt() module; and

20 disconnecting the identified connection sockets.

22 25. The method in accordance with Claim 24, further comprising:

23 specifying a grace period between the time the backlog queue is determined
24 to be used and the time the identified connection sockets are disconnected, wherein

1 the disconnection is performed only if the backlog queue still has entries after the
2 grace period.
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24

ABSTRACT OF THE DISCLOSURE

A way of reducing the impact of denial of service attacks is presented. For each connection request received by a server, the server attempts to establish a connection to accommodate the corresponding request. For each connection request that the server cannot currently handle, the connection request is placed in a backlog queue for future handling. If one or more of the backlog queues have entries, connection sockets that have connections but no received request data are identified and disconnected. Such connection sockets would be highly suspect of being generated as a result of denial of service attacks. Upon disconnection, resources are freed for legitimate requests thereby improving server performance even during denial of service attacks.

G:\DATA\PAT\WORDPAT\13768143.doc




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5